

AMENDMENTS TO THE SPECIFICATION

Please **revise paragraph [0032] of the specification** as follows:

[0032] As shown in Figure 3A, the resin member forming the vehicle seat 90 has a certain degree of vertical thickness to function as a buffer for the rider. The vehicle seat 90 includes an internal member 92 extending between a front and a rear of the vehicle seat 90. A front side of the internal member 92 faces substantially in a forward direction, and a rear side of the internal member 92 faces substantially in a rearward direction. Vehicle seat 90 has a seat surface 91, a central portion of which the rider sits upon. Therefore, when the RFID is attached to one of the central positions 71b, 71c, 71d, or 71e of the internal member 92, the distance between the RFID and a central portion of the seat surface 91 is comparatively long. On the contrary, when the RFID is attached to the front or rear ~~part of~~ the side of the internal member 92 of the vehicle seat 90, such as the positions 71a or 71f within the vehicle seat 90, the distance to the front or rear of the seat surface 91 is comparatively short, respectively. Therefore, when the distance that read/write signals (electromagnetic waves) for the RFID travel over is comparatively short, the RFID is provided at the position whose distance to the front or rear of the seat surface is relatively short, for example the positions 71a or 71f. This allows the reader to be brought closer to the RFID, thus facilitating reading and writing.